

15 / 20 / 25 W LED

# Gamme BOOSTER

DOWNLIGHT


DOWNLIGHT



## LES PLUS PRODUIT

700 G	850°	Dim phase	DALI	RoHS Norme	IP 44	IRC 82	15W:350ma 20W:500ma 25W:600ma	60°	SDCM <4	CE
IK 07	EPSTAR	Push dim	TRIDONIC	RoHS Norme	IP 44	IRC 82	15W:350ma 20W:500ma 25W:600ma	60°	SDCM <4	CE
IP 44	TRIDONIC	Push dim	TRIDONIC	RoHS Norme	IP 44	IRC 82	15W:350ma 20W:500ma 25W:600ma	60°	SDCM <4	CE
IP 44	TRIDONIC	Push dim	TRIDONIC	RoHS Norme	IP 44	IRC 82	15W:350ma 20W:500ma 25W:600ma	60°	SDCM <4	CE

Ø Installation 140 mm



# DOWNLIGHT BOOSTER

15/20/25 W	Références Luminaire	Descriptions Luminaire
3000 k	LT-DW150WW	Downlight led 15/20/25W 3000K sans driver
4000 k	LT-DW150	Downlight led 15/20/25W 4000K sans driver

	Drivers indispensables	Descriptions Drivers
15 W	LF15-350MA	Driver led LIFUD 15W non Dimmable pour LT-DW150
	LCBI-15-350SR	Driver Tridonic variation à la phase
20 W	LF20-500MA	Driver led LIFUD 20W non Dimmable pour LT-DW150
25 W	LF25-600ma	Driver led LIFUD 25W non Dimmable pour LT-DW150
15, 20 & 25W	LCA-25-350-1050SR	Driver Tridonic Dali /PUSH DIM

**GARANTIE**  
3 ANS

## DONNÉES TECHNIQUES

	3000 K	4000 K	Dim Phase	Non Dimmable	DALI/ Push Dim	1/10 V	Finition noire	Finition blanche
15 W	1323 lm	1480 lm	●	●	●	●	RAL 9017	RAL 9003
20 W	1800 ml	1950 lm	●	●	●	●	RAL 9017	RAL 9003
25 W	2054 lm	2200 lm	●	●	●	●	RAL 9017	RAL 9003

## ÉCLAIREMENT LUMINEUX

15 W	h (m)	D (m)	Em (lx)
60°	à 1 m	1,1	681
	à 2 m	2,2	208
	à 3 m	3,3	109
	à 4 m	4,4	71
	à 5 m	5,5	52

20 W	h (m)	D (m)	Em (lx)
60°	à 1 m	1,1	935
	à 2 m	2,2	285
	à 3 m	3,3	150
	à 4 m	4,4	97
	à 5 m	5,5	71

25 W	h (m)	D (m)	Em (lx)
60°	à 1 m	1,1	1054
	à 2 m	2,2	322
	à 3 m	3,2	169
	à 4 m	4,3	110
	à 5 m	5,4	80