

9,6 W MONO LED

Gamme **KIFF**

DOWNLIGHT

DOWNLIGHT



### LES PLUS PRODUIT

300 G	CE	850°	IRC 92	L80B10	RoHS Norme	IP 44	Courant driver 500 ma	SDCM 2-3
UGR <19	850°	IK 07	Dim phase	BRIDGELUX	ø 83mm	IP 44	Courant driver 500 ma	SDCM 2-3
48°	IRC 92	IK 07	Dim phase	TRIDONIC	48°	IP 44	Courant driver 500 ma	SDCM 2-3
48°	IRC 92	IK 07	Dim phase	TRIDONIC	48°	IP 44	Courant driver 500 ma	SDCM 2-3
48°	IRC 92	IK 07	Dim phase	TRIDONIC	48°	IP 44	Courant driver 500 ma	SDCM 2-3



DOWNLIGHT

**KIFF**

### DONNÉES TECHNIQUES

3000 K	4000 K	Dim Phase	Non Dimmable	DALI/ Push Dim	1/10 V	Finition noire	Finition blanche
9,6 W	740 lm	820 lm	●	●	●	●	●
							RAL 9003

**GARANTIE**  
5 ANS

9,6 W	Références Luminaires	Descriptions Luminaires
3000 k	KIFF-9WW	Downlight LED 9W 3000k asymétrique + driver non Dimmable
4000 k	KIFF-9	Downlight LED 9W 4000k asymétrique + driver non Dimmable
	Drivers supplémentaires en option	Descriptions Drivers
9,6 W	LCBI-10-500	Driver Tridonic variation à la phase
	LCA-25-350-1050SR	Driver Tridonic Dali /PUSH DIM

### ÉCLAIREMENT LUMINEUX

